MULE SX™ 4x4 XC









4.2 gal

POWER

Engine 4-stroke, single-cylinder, OHV, air-cooled

Displacement 401cc

Maximum Torque 21.4 lb-ft @ 2,400 rpm

Bore x Stroke 3.23 x 2.99 in

Compression Ratio 8.6:1

Fuel System Fuel injection

Transmission Continuously Variable Transmission (CVT) with (H,L,N,R)

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

Engine Braking No

Alternator Output 22.9 amp

(max)

CAPABILITY

MacPherson Strut/3.1 in Front Suspension / **Wheel Travel**

Rear Suspension / Wheel Travel

Unit Swingarm/3.1 in

Front Tires 26x9.00-12 **Rear Tires** 26x9.00-12

Rack-and-pinion Steering

Park Brake Type Independent, Mechanical Drum

Front Brakes Drum **Rear Brakes** Drum **Ground Clearance** 8.1 in

Turning Radius 11.8 ft

Cargo Bed

Dimensions (LxWxH)

Cargo Bed Load

Capacity

Fuel Capacity

Payload Capacity 900 lb

Seating Capacity

1,100 lb** **Towing Capacity**

Lighting (2) Halogen headlights, tail/brake lights

35.6 x 40.9 x 9.6 in

DETAILS

Overall Length 106.7 in **Overall Width** 52.6 in **Overall Height** 73.4 in **Curb Weight** 1,082.7 lb*

Wheelbase 70.1 in

Instruments Fuel gauge, hour meter, oil temp light, parking brake

Wheel Type Steel

Color Choices Firecracker Red, Timberline Green

Warranty Kawasaki STRONG 3-Year Limited Warranty

Scan with camera to view videos, key features and more.



