CONCOURS®14 ABS







P	N	V	V	FI	R
	u	\mathbf{A}^{\prime}	٧ı	LI	М

Engine 4-stroke, 4-cylinder, DOHC, 4-valve, liquid-

cooled

Displacement 1,352cc

Bore x Stroke 84.0 x 61.0mm

Compression

Ratio

10.7:1

Maximum

Torque

100.5 lb-ft

Fuel System

DFI® with 40mm throttle bodies (4)

Ignition

TCBI with electronic advance

Transmission

6-speed

Final Drive

Tetra-Lever shaft drive

Electronic Rider

Aids

Kawasaki Advanced Coactive-Braking

Technology (K-ACT) ABS System, Kawasaki

Traction Control (KTRC)

PERFORMANCE

Front Suspension / **Wheel Travel** 43mm inverted, telescopic fork with adjustable rebound damping and spring preload/4.4 in

Rear Suspension / Wheel Travel

Tetra-Lever with stepless rebound damping adjustment and remote spring preload adjuster/5.4 in

Front Brakes Dual floating 310mm petal-style discs with four-piston calipers, ABS

Rear Brakes Single 270mm petal-style disc, single-piston

caliper, ABS

120/70 ZR-17

190/50 ZR-17

DETAILS

Front Tire

Rear Tire

Monocoque Aluminum **Frame Type**

Rake/Trail 26.0/4.4 in

Overall Length 87.8 in

Overall Width 31.1/39.4 wo/w saddlebags

Overall Height 52.9 in/57.7 in (windshield down/up)

4.9 in Ground Clearance

Seat Height 32.1 in

Curb Weight 690.2 lb (672.5 w/o saddlebags)*

Fuel Capacity 5.8 gal

Wheelbase 59.8 in

Special Features Electically adjusted windshield

Color Choices Metallic Spark Black

Warranty 36 Month Limited Warranty

Scan with camera to view videos. key features and more.

