MULE PRO-MX™ EPS









9.5 gal

1200 lb

POWER

Engine 4-stroke, single cylinder, SOHC, 4-valve liquid-cooled

Displacement 695cc

Maximum Torque 42.7 lb-ft @ 5000 rpm

Bore x Stroke 4.02x3.35 in

Compression Ratio 10.3:1

Fuel System DFI® with 44mm throttle body

Transmission Continuously Variable Transmission (CVT) with

centrifugal clutch, (H,L,N,R)

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

Engine Braking

Alternator Output 35.7 amp

(max)

CAPABILITY

Front Suspension / Double wishbone/8.6 in **Wheel Travel**

Rear Suspension / Wheel Travel

Double wishbone/9.1 in

Front Tires 25x8.00-12, radial **Rear Tires** 25x10.00-12, radial

Electric Power Steering (EPS), Tilt steering **Steering**

Park Brake Type Independent, Mechanical Disc **Front Brakes** Dual Disc, 2 piston caliper **Rear Brakes** Dual Disc, 1 piston caliper

Ground Clearance 10.6 in

Turning Radius 14.0 ft

Cargo Bed 33.4 x 44.1 x 9.1 in

Dimensions (LxWxH)

Cargo Bed Load

Fuel Capacity

Capacity

Payload Capacity

Seating Capacity

Towing Capacity 1500 lb

Lighting (2) Halogen headlights. (2) LED headlights

699 lb (600 lb California models)

DETAILS

Overall Length 110.0 in **Overall Width** 60.0 in **Overall Height** 74.4 in **Curb Weight** 1587.6 lb*

Wheelbase 78.9 in

Instruments

Multi-function display includes digital speedometer, fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, EPS warning indicators, neutral, reverse and parking indicators, differential indicator lamp, seatbelt

reminder lamps

Wheel Type

Color Choices Timberline Green, Bright White

Warranty Kawasaki 3-Year Limited Warranty

Scan with camera to view videos, key features and more.

