## **MULE™ 4010 4x4**









Drum

6.9 in

## **POWER**

4-stroke, 2-cylinder, OHV, 90° V Liquid-cooled **Engine** 

Displacement 617cc

**Maximum Torque** 34.7 lb-ft @ 2,500 rpm

**Bore x Stroke** 2.99x2.68 in

**Compression Ratio** 10:3:1

**Fuel System** DFI® with 34mm Mikuni throttle body

**Transmission** Continuously Variable Transmission (CVT) with

(H,L,N,R)

**Final Drive** Selectable 2WD/4WD, shaft. Dual mode rear

differential with differential lock

**Engine Braking** 

**Alternator Output** 23 amp

(max)

**Fuel Capacity** 6.3 gal **Turning Radius** 11.2 ft 46.3 x 51.6 x 11.4 in **Cargo Bed Dimensions** (LxWxH) **Cargo Bed Load** 800 lb **Capacity Payload Capacity** 1,327 lb

**Seating Capacity** 

**Towing Capacity** 1,200 lb

Lighting (2) Halogen headlights (2) tail/brake lights

## **CAPABILITY**

Front Suspension / MacPherson Strut/3.9 in **Wheel Travel** 

**Rear Suspension / Wheel Travel** 

DeDion Axle/2.8 in

**Front Tires** 23x11.00-10 **Rear Tires** 23x11.00-10

**Steering** Electric Power Steering (EPS)

**Park Brake Type** Independent, Mechanical Drum

**Front Brakes** Drum

## **DETAILS**

**Rear Brakes** 

**Ground Clearance** 

**Overall Length** 116.7 in **Overall Width** 62.0 in **Overall Height** 75.8 in **Curb Weight** 1,433.3 lb\* Wheelbase 73.6 in

Instruments Parking brake warning light, coolant temperature warning light, 12V DC outlet, fuel gauge, hour meter

**Wheel Type** Steel

**Color Choices** Timberline Green, Dark Royal Red

Warranty Kawasaki STRONG 3-Year Limited Warranty

Scan with camera to view videos, key features and more.

