## MULE SX<sup>™</sup> 4x4 FI









## **POWER**

**Engine** 4-stroke, single-cylinder, OHV, air-cooled

Displacement 401cc

**Maximum Torque** 21.4 lb-ft @ 2,400 rpm

**Bore x Stroke** 3.23x2.99 in

**Compression Ratio** 8.6:1

**Fuel System Fuel Injection** 

**Transmission** Continuously Variable Transmission (CVT) with (H,L,N,R)

**Final Drive** Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

**Engine Braking** No

**Alternator Output** 

(max)

22.9 amp

## **CAPABILITY**

MacPherson Strut/3.1 in Front Suspension / **Wheel Travel** 

**Rear Suspension /** 

**Wheel Travel** 

Unit Swingarm/3.1 in

**Front Tires** 24x9.00-10

24x11.00-10

**Rear Tires** 

Steering

Rack-and-pinion

**Park Brake Type** 

Independent, Mechanical Drum

**Front Brakes** 

Drum

**Rear Brakes** Drum **Ground Clearance** 6.7 in

**Fuel Capacity** 4.2 gal

**Turning Radius** 10.8 ft

**Cargo Bed** 

**Dimensions (LxWxH)** 

**Cargo Bed Load** 

Capacity

**Payload Capacity** 915 lb

**Seating Capacity** 

1,100 lb\*\* **Towing Capacity** 

Lighting (2) Halogen headlights, tail/brake lights

35.6 x 40.9 x 9.6 in

399 lb

## **DETAILS**

**Overall Length** 106.7 in

**Overall Width** 52.6 in

**Overall Height** 70.9 in

**Curb Weight** 1,031.9 lb\*

Wheelbase 70.1 in

Instruments Fuel gauge, hour meter, oil temp light, parking brake

light

**Wheel Type** Steel

**Color Choices** Timberline Green, Dark Royal Red

Warranty Kawasaki STRONG 3-Year Limited Warranty

Scan with camera to view videos, key features and more.



\*Requires Optional Hitch