## <sup>2024</sup> **KX<sup>™</sup>250X**







## POWER

Engine	4-stroke single, DOHC, liquid-cooled
Displacement	249cc
Bore x Stroke	78.0 x 52.2mm
Compression Ratio	14.1:1
Fuel System	DFI® with 44mm Keihin throttle body and dual injectors
Ignition	Digital CDI
Transmission	5-speed, return shift, with wet multi-disc manual clutch
Final Drive	Chain
Electronic Rider Aids	Launch Control Mode

Front Tire	80/100-21
Rear Tire	110/100-18
Front Brakes	Single semi-floating 270mm Braking petal disc with dual-piston caliper
Rear Brakes	Single 240mm Braking petal disc with single-piston caliper

## DETAILS

Frame Type	Aluminum perimeter
Rake/Trail	27.8°/4.8 in
Overall Length	85.4 in
Overall Width	32.3 in
Overall Height	49.6 in
Ground Clearance	13.0 in
Seat Height	37.2 in
Curb Weight	230.1 lb* without fuel / 240.2 lb*
Fuel Capacity	1.64 gal
Wheelbase	58.3 in
Color Choices	Lime Green
Warranty	Not Available

## PERFORMANCE

Front	48mm inverted telescopic coil-spring fork
Suspension /	with 23-way compression damping and 20-
Wheel Travel	way rebound damping/12.4 in
Rear Suspension / Wheel Travel	Uni-Trak <sup>®</sup> with dual-range (2.25 turns high speed/21-way low-speed) compression damping, 38-way rebound damping and adjustable preload/12.4 in

Scan with camera to view videos, key features and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2024 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit bermuda.kawasaki-la.com for full product details.