
MULE PRO-FXT™ 1000 LE









POWER

Engine 4-stroke, 2-cylinder, DOHC, liquid-cooled, gas

999cc Displacement

Maximum Torque 61.5 lb-ft

Bore x Stroke 92.0 x 75.1mm

Compression Ratio 10.1:1

DFI® with 38mm throttle body **Fuel System**

Continuously Variable Transmission (CVT) with (L,H,N,R) **Transmission**

Final Drive Selectable 2WD/4WD, shaft Dual mode rear differential

with differential lock

Engine Braking Yes

Alternator Output 90 amp

(max)

Ground Clearance 12.6 in (max), 11.6 in (std)

Fuel Capacity 7.9 gal

Turning Radius 16.0 ft

Cargo Bed 42.7 x 53.7 x 11.0 in (3-person) / 22.0 x 53.7 x 11.0 in (6-Dimensions (LxWxH)

1,913.9 lb* / 1,916.1 lb* CA Model

Multi-function display includes digital speedometer, fuel gauge, odometer, hour meter, clock, dual trip meters,

2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, fuel injection warning

indicator, CVT and EPS warning indicators, neutral, reverse

and parking indicators, seatbelt reminder lamps

person)

Cargo Bed Load 999 lb (3-person) / 350 lb (6-person) / 348 lb CA Model

Capacity

DETAILS

Overall Length

Overall Width

Overall Height

Curb Weight

Wheelbase

Instruments

Payload Capacity 1,616.3 lb / 1,263.5 lb CA Model

Seating Capacity 3-person (1 row), 6 person (2 row)

135.8 in

64.0 in

80.9 in

92.3 in

Towing Capacity 2.000 lb

Lighting (2) Halogen headlights. (2) LED headlights

Double wishbone/11.0 in Front Suspension / **Wheel Travel**

Wheel Type

Additional Features Roof, Additional Front Cup Holders

Alloy

Color Choices Metallic Onyx Black, Metallic Sierra Blue

Kawasaki STRONG 3-Year Limited Warranty Warranty

CAPABILITY

Rear Suspension / Double wishbone/10.1 in Wheel Travel **Front Tires** 26 x 9.00-12, radial **Rear Tires** 26 x 11.00-12, radial Steering Electric Power Steering (EPS), Tilt steering **Park Brake Type** Independent, Mechanical Disc **Front Brakes** Dual Disc, 2 piston caliper Rear Brakes Dual Disc, 1 piston caliper



