
MULE SX™ 4x4 FE









POWER

Engine 4-stroke, single-cylinder, OHV, air-cooled

Displacement 401cc

Maximum Torque 21.4 lb-ft @ 2,400 rpm

Bore x Stroke 3.23 x 2.99 in

Compression Ratio 8.6:1

Fuel System Fuel Injection

Transmission Continuously Variable Transmission (CVT) with (H,L,N,R)

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

Engine Braking No

Alternator Output 22.9 amp

(max)

Ground Clearance 6.7 in

Turning Radius 10.8 ft

Cargo Bed

Dimensions (LxWxH)

Cargo Bed Load 399

Capacity

Fuel Capacity

capacity

Payload Capacity 915 lb

4.2 gal

Seating Capacity 2

Towing Capacity 1,100 lb**

Lighting (2) Halogen headlights, tail/brake lights

35.6 x 40.9 x 9.6 in

CAPABILITY

Front Suspension / MacPherson Strut/3.1 in Wheel Travel

Rear Suspension / Wheel Travel

Rear Tires

Unit Swingarm/3.1 in

24x11.00-10

Front Tires 24x9.00-10

Steering Rack-and-pinion

Park Brake Type Independent, Mechanical Drum

Front Brakes Drum

Rear Brakes Drum

DETAILS

Overall Length 106.7 in

Overall Width 52.6 in

Overall Height 72.4 in

Curb Weight 1,056.2 lb*

Wheelbase 70.1 in

Instruments Fuel gauge, hour meter, oil temp light, parking brake

light / horn

Wheel Type Stee

Additional Features Roof, Horn, Universal Key, High Visibility Orange

Seatbelts

Color Choices Bright White

Warranty Kawasaki STRONG 3-Year Limited Warranty

Scan with camera to view videos, key features and more.

