

ALL-NEW 2024

RIDGE® RANCH EDITION



METALLIC STARDUST WHITE



POWER

|                         |  |
|-------------------------|--|
| Engine                  | 4-stroke, DOHC, 4-valve In-Line Four-Cylinder, liquid-cooled |
| Displacement            | 999cc  |
| Maximum Horsepower      | 92.0 hp <sup>1</sup> @ 8,500 rpm                             |
| Maximum Torque          | 65.8 lb-ft @ 5,500 rpm                                       |
| Bore x Stroke           | 73.4 x 59.0mm  |
| Compression Ratio       | 10.6:1   |
| Fuel System             | EFI  |
| Ignition                | TCBI with Digital Advance                                    |
| Starting System         | Electric   |
| Transmission            | Continuously Variable Transmission (CVT) with (H,L,N,R)      |
| Final Drive             | Selectable 4WD with locking rear differential, shaft         |
| Engine Braking          | Yes  |
| Alternator Output (max) | 85 amp   |
| Electronic Rider Aids   | Power Modes, Economical Riding Indicator                     |

CAPABILITY

|                                 |  |
|---------------------------------|--|
| Front Suspension / Wheel Travel | Long-Travel, Double Wishbone/12.7 in                   |
| Rear Suspension / Wheel Travel  | Long-Travel, Double Wishbone/12.7 in                   |
| Front Tires                     | Duro 27 x 9-14   |
| Rear Tires                      | Duro 27 x 11-14  |
| Wheel Type                      | 14" Aluminum   |
| Steering                        | Rack-and-pinion w/ Electric Power Steering (EPS)       |
| Front Brakes                    | Dual hydraulic 249mm discs with two-piston calipers    |
| Rear Brakes                     | Dual hydraulic 249mm discs with single-piston calipers |

|                              |  |
|------------------------------|--|
| Ground Clearance             | 12.6/13.6 in (max preload); 12.6 in CA Model |
| Fuel Capacity                | 12.9 gal                                     |
| Turning Radius               | 15.0 ft                                      |
| Cargo Bed Dimensions (LxWxH) | 37.6 x 49.0 x 12.8 in                        |
| Cargo Bed Load Capacity      | 1,000/600 lb CA Model                        |
| Payload Capacity             | 1,499/1,100 lb CA Model                      |
| Seating Capacity             | 3, bench seat                                |
| Towing Capacity              | 2,500 lb                                     |
| Lighting                     | All-LED lighting                             |

DETAILS

|                     |  |
|---------------------|--|
| Frame               | Ladder type, tubular steel   |
| Overall Length      | 126.4 in   |
| Overall Width       | 64.0 in  |
| Overall Height      | 81.9 in  |
| Curb Weight         | 1,909.5/1,911.7 lb* CA Model   |
| Wheelbase           | 90.7 in  |
| Instruments         | Digital speedometer, tachometer, fuel gauge, odometer, dual trip meters, total time, trip time, average speed, gear indicator, Driving Mode, Power Mode, clock, water temperature, battery voltage, oil change reminder, Bluetooth indicator, Economical Riding Indicator, maintenance reminder, high beam, neutral, reverse, and warning lights (battery, EPS, CVT, seatbelt, parking indicator, oil pressure, water temperature) |
| Additional Features | WARN® VRX 45 Powersport Winch, Adjustable driver's seat, ERGO-FIT®, Full-color TFT Instrumentation with Smartphone Connectivity via RIDEOLGY THE APP Powersports, USB ports, KQR™ system compatible  |
| Color Choices       | Metallic Stardust White  |
| Warranty            | Kawasaki STRONG 3-Year Limited Warranty  |

Scan with camera to view videos, key features and more.



<sup>\*</sup>Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).  
<sup>1</sup>This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.  
Specifications subject to change. Visit [bermuda.kawasaki-la.com](http://bermuda.kawasaki-la.com) for full product details.