## 2025 **KX**<sup>™</sup>112







## **Front Brakes** Single 220mm petal disc with dual-piston POWER caliper **Rear Brakes** Single 184mm petal disc with single-piston Engine 2-stroke, single-cylinder with exhaust power caliper valve (KIPS), liquid-cooled Displacement 112cc DETAILS **Bore x Stroke** 52.5 x 51.6mm High-tensile steel perimeter design with **Frame Type** 9.9:1 (low speed) / 8.6:1 (high speed) Compression subframe member Ratio Rake/Trail 29.0°/4.3 in 28mm Keihin carburetor **Fuel System Overall Length** 75.6 in Ignition CDI with Digital Advance **Overall Width** 30.1 in Transmission 6-speed, return shift, with wet multi-disc manual clutch **Overall Height** 45.3 in **Final Drive** Chain Ground 13.0 in Clearance PERFORMANCE **Seat Height** 34.3 in **Curb Weight** 169.7 lb\* Front 36mm inverted telescopic cartridge fork with Suspension / 20-way compression damping/10.8 in **Fuel Capacity** 1.32 gal Wheel Travel Wheelbase 51.6 in Rear Uni-Trak<sup>®</sup> gas charged shock with piggyback Suspension / reservoir with 24-way compression and 21-**Special ERGO-FIT®** Wheel Travel way rebound damping plus adjustable spring **Features** preload/10.8 in **Color Choices** Lime Green **Front Tire** 70/100-19 Not Available Warranty

**Rear Tire** 

Scan with camera to view videos. key features and more.



90/100-16

\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit bermuda.kawasaki-la.com for full product details.