MULE™ 4010 TRANS4x4® FE









POWER

Engine 4-stroke, 2-cylinder, OHV, 90° V-twin, Liquid-cooled

Displacement 617cc

Maximum Torque 34.7 lb-ft @ 2,500 rpm

Bore x Stroke 76.0 x 68.0mm

Compression Ratio 10:3:1

Fuel System DFI® with 34mm Mikuni throttle body

Transmission Continuously Variable Transmission (CVT) with (H,L,N,R)

Final Drive Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

Engine Braking

Alternator Output 23 amp

(max)

Ground Clearance 7.7 in

Fuel Capacity 6.3 gal

Turning Radius 12.8 ft

50.4 x 47.6 x 11.2 in (2-person) / 30.3 x 47.6 x 11.2 in (4-**Cargo Bed Dimensions (LxWxH)**

800 lb (2-person) / 401 lb (4-person)

Capacity

Cargo Bed Load

1,330 lb **Payload Capacity**

Seating Capacity

Towing Capacity 1,200 lb

Lighting (2) Halogen headlights, (2) tail/brake lights

CAPABILITY

Front Suspension / MacPherson Strut/3.9 in **Wheel Travel**

Rear Suspension / DeDion Axle/2.8 in **Wheel Travel**

Front Tires 23 x 11-10 **Rear Tires** 23 x 11-10

Rack-and-pinion w/ Electric Power Steering (EPS) Steering

Park Brake Type Independent, mechanical drum

Front Brakes Drum **Rear Brakes** Drum

DETAILS

Curb Weight

Overall Length 128.5 in **Overall Width** 58.5 in

Overall Height 78.1 in

Wheelbase 85.2 in

Instruments Parking brake warning light, coolant temperature

warning light, 12V DC outlet, fuel gauge, hour meter

Additional Features Roof, Horn, Universal Key, High Visibility Orange

Seatbelts

1,614.1 lb*

Color Choices Bright White

Kawasaki STRONG 3-Year Limited Warranty Warranty

Scan with camera to view videos, key features and more.



