2025 MULE PRO-FX[™] 1000 HD EDITION







POWER

Engine	4-stroke, 2-cylinder, DOHC, liquid-cooled, gas	
Displacement	999cc	
Maximum Torque	61.5 lb-ft @ 4,500 rpm	
Bore x Stroke	92.0 x 75.1mm	
Compression Ratio	10.1:1	
Fuel System	DFI® with 38mm throttle body	
Transmission	Continuously Variable Transmission (CVT) with (H,L,N,R)	
Final Drive	Selectable 2WD/4WD, shaft. Dual mode rear differential with differential lock	
Engine Braking	Yes	
Alternator Output (max)	90 amp	

Ground Clearance	11.9 in (max), 11.8 in (std)
Fuel Capacity	7.9 gal
Turning Radius	16.0 ft
Cargo Bed Dimensions (LxWxH)	54.1 x 53.3 x 11.0 in
Cargo Bed Load Capacity	999/600 lb CA Model
Payload Capacity	1,616.3/1,263.5 lb CA Model
Seating Capacity	3
Towing Capacity	2,000 lb
Lighting	(2) Halogen headlights, (2) LED headlights

DETAILS

		Overall Length	136.6 in	
		Overall Width	64.0 in	
		Overall Height	81.1 in	
	Double wishbone/11.0 in	Estimated Dry Weight	1,816.9/1,819.1 lb** CA Model	
	Double wishbone/10.1 in	Curb Weight	1,891.9/1,894.1 lb* CA Model	
		Wheelbase	92.3 in	
	26 x 9-12, radial	Instruments	Multi-function display includes digital speedometer, fuel gauge,	
	26 x 11-12, radial		odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure	
	Steel		warning indicator, fuel injection warning indicator, CVT warning indicator, neutral, reverse and parking indicators, seatbelt	
	Rack-and-pinion		reminder lamps	
	Independent, mechanical disc	Additional Features	Roof, Rear Bumper, Additional Under Seat Storage Bin,	
	Dual disc, 2-piston caliper	Rearview Mirror, Hydraulic Cargo Bed Lift, Self-Leveling F Suspension, Anti-cinch Seatbelts		
	Dual disc, 1-piston caliper	Color Choices	Firecracker Red	
		Warranty	Kawasaki STRONG 3-Year Limited Warranty	

Scan with camera to view videos, key features and more.

CAPABILITY

Front Suspension / Wheel Travel Rear Suspension / Wheel Travel Front Tires

Rear Tires

Wheel Type Steering Park Brake Type Front Brakes Rear Brakes



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). **Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). All MULE™ PRO Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of ISO 3471.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear protective gear appropriate for the use of this vehicle. Never operate under the influence of drugs or alcohol. Protect the environment. The Kawasaki MULE™ side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. Obey the laws and regulations that control the use of your vehicle. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit bermuda.kawasaki-la.com for full product details.