## **MULE PRO-MX™ SE**







n	n	١	M	Г	n
Г	u	ľ	N	E	π

4-stroke, single cylinder, SOHC, 4-valve, liquid-cooled **Engine** 

**Displacement** 695cc

42.7 lb-ft @ 5,000 rpm **Maximum Torque** 

**Bore x Stroke** 102.0 x 85.0mm

**Compression Ratio** 10.3:1

**Fuel System** DFI® with 44mm throttle body

**Transmission** Continuously Variable Transmission (CVT) with centrifugal

clutch, (H,L,N,R)

**Final Drive** Selectable 2WD/4WD, shaft. Dual mode rear differential

with differential lock

**Engine Braking** Yes

**Alternator Output** 

35.7 amp

## CAPABILITY

Front Suspension / **Wheel Travel** 

Double wishbone / 8.6 in

Rear Suspension / **Wheel Travel** 

Double wishbone/9.1 in

**Front Tires** 25 x 8-12, radial

**Rear Tires** 25 x 10-12, radial

Steering Electric Power Steering (EPS), Tilt steering

**Park Brake Type** Independent, mechanical disc

**Front Brakes** Dual disc, 2-piston caliper

**Rear Brakes** Dual disc, 1-piston caliper **Ground Clearance** 10.6 in

**Fuel Capacity** 9.5 gal

**Turning Radius** 14.0 ft

Cargo Bed

**Dimensions (LxWxH)** 

**Cargo Bed Load** 699 lb / 600 lb CA Model

Capacity

**Payload Capacity** 1,200 lb

**Seating Capacity** 

**Towing Capacity** 1,500 lb

Lighting (2) Halogen headlights, (2) LED headlights

33.4 x 44.1 x 9.1 in

## **DETAILS**

**Overall Length** 110.0 in

**Overall Width** 60.0 in

**Overall Height** 75.8 in

**Curb Weight** 1,622.9 lb\* / 1,625.1 lb\* CA Model

Wheelbase 78.9 in

Instruments Multi-function display includes digital speedometer, fuel

> gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, EPS warning indicators, neutral, reverse and parking indicators, differential indicator lamp, seatbelt

reminder lamps

**Additional Features** Roof, WARN® VRX 35 Winch, Cast Aluminum Wheels,

Painted Body Panels

**Color Choices** Gold

Kawasaki STRONG 3-Year Limited Warranty Warranty

Scan with camera to view videos, key features and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). All MULE™ PRO Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of ISO 3471