

2027

BRUTE FORCE® 750

Kawasaki

Let the Good Times Roll®



 FIRECRACKER RED



POWER

|                    |                                                                         |
|--------------------|-------------------------------------------------------------------------|
| Engine             | 4-stroke, V-twin, SOHC, liquid-cooled                                   |
| Displacement       | 749cc                                                                   |
| Bore x Stroke      | 85.0 x 66.0mm                                                           |
| Compression Ratio  | 9.3:1                                                                   |
| Maximum Horsepower | 50.0 hp <sup>1</sup> @ 6,750 rpm                                        |
| Maximum Torque     | 42.8 lb-ft @ 4,750 rpm                                                  |
| Fuel System        | DFI® with two 34mm throttle bodies                                      |
| Ignition           | Digital DC-CDI                                                          |
| Transmission       | Automatic Continuously Variable Transmission (CVT) with (H,L,N,R)       |
| Final Drive        | Selectable 2WD/4WD with variable control front differential lock, shaft |

|                           |                  |
|---------------------------|------------------|
| Fuel Capacity             | 5.0 gal          |
| Steering                  | Rack-and-pinion  |
| Turning Radius            | 10.5 ft          |
| Towing Capacity           | 1,250 lb         |
| Total Rack Capacity       | 264.5 lb         |
| Rack Capacity, Front/Rear | 88.0/176.0 lb    |
| Lighting                  | All-LED lighting |

CAPABILITY

|                                 |                                                            |
|---------------------------------|------------------------------------------------------------|
| Front Suspension / Wheel Travel | Double wishbone, adjustable spring preload/6.9 in          |
| Rear Suspension / Wheel Travel  | Double wishbone, adjustable spring preload/7.4 in          |
| Front Tires                     | AT 25 x 8-12                                               |
| Rear Tires                      | AT 25 x 10-12                                              |
| Front Brakes                    | Dual hydraulic 176mm discs with 2-piston calipers          |
| Rear Brakes                     | Sealed, oil-bathed, multi-disc with independent park brake |
| Ground Clearance                | 9.0 in/9.7 in (max preload)                                |
| Starting System                 | Electric                                                   |

DETAILS

|                      |                                                                                                                                                                                                                                                                                                       |
|----------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Frame Type           | Double-cradle, high-tensile tubular steel                                                                                                                                                                                                                                                             |
| Tread Width          | 37.0/35.6 in                                                                                                                                                                                                                                                                                          |
| Overall Length       | 86.0 in                                                                                                                                                                                                                                                                                               |
| Overall Width        | 46.1 in                                                                                                                                                                                                                                                                                               |
| Overall Height       | 47.6 in                                                                                                                                                                                                                                                                                               |
| Seat Height          | 35.2 in                                                                                                                                                                                                                                                                                               |
| Estimated Dry Weight | 661.5 lb**                                                                                                                                                                                                                                                                                            |
| Curb Weight          | 707.8 lb*                                                                                                                                                                                                                                                                                             |
| Wheelbase            | 50.6 in                                                                                                                                                                                                                                                                                               |
| Instruments          | Digital speedometer, 2WD/4WD drive indicator, fuel gauge, odometer, dual trip meters, dual hour meter, clock (12h/24h), battery voltage, Kawasaki service reminder, oil change reminder, high beam, neutral, reverse, and warning lights (engine, coolant temperature, CVT, oil, and battery voltage) |
| Special Features     | Full-color TFT Instrumentation w/ Smartphone Connectivity via RIDELOGY THE APP POWERSPORTS, KQR™ system                                                                                                                                                                                               |
| Color Choices        | Firecracker Red                                                                                                                                                                                                                                                                                       |
| Warranty             | 12 Month Limited Warranty                                                                                                                                                                                                                                                                             |

Scan with camera  
to view videos,  
key features  
and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

\*\*Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

<sup>1</sup>This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Warning: ATVs can be hazardous to operate. For your safety: Always wear a helmet, eye protection, and protective clothing. Never carry a passenger. Never ride under the influence of drugs or alcohol. Never ride on public roads or pavement. Avoid excessive speeds and stunt driving. Be extra careful on difficult terrain. Kawasaki ATVs with engines over 90cc are intended for use only by persons 16 years of age or older. Kawasaki also recommends that all ATV riders take a training course. For more information, see your dealer, call the ATV Safety Institute at 1-800-887-2887, or go to [www.atvsafety.org](http://www.atvsafety.org). © 2026 Kawasaki Motors Corp., U.S.A.

Specifications subject to change. Visit [bermuda.kawasaki-la.com](http://bermuda.kawasaki-la.com) for full product details.