

2027

BRUTE FORCE® 750 SE EPS CAMO

Kawasaki

Let the Good Times Roll®



 TRUETIMBER® STRATA



POWER		Turning Radius	
Engine	4-stroke, V-twin, SOHC, liquid-cooled	Towing Capacity	1,250 lb
Displacement	749cc	Total Rack Capacity	264.5 lb
Bore x Stroke	85.0 x 66.0mm	Rack Capacity, Front/Rear	88.0/176.0 lb
Compression Ratio	9.3:1	Lighting	All-LED lighting
Maximum Horsepower	50.0 hp ¹ @ 6,750 rpm	DETAILS	
Maximum Torque	42.7 lb-ft @ 4,750 rpm	Frame Type	Double-cradle, high-tensile tubular steel
Fuel System	DFI® with two 34mm throttle bodies	Tread Width	37.0/35.6 in
Ignition	Digital DC-CDI	Overall Length	86.0 in
Transmission	Automatic Continuously Variable Transmission (CVT) with (H,L,N,R)	Overall Width	46.1 in
Final Drive	Selectable 2WD/4WD with variable control front differential lock, shaft	Overall Height	47.6 in
CAPABILITY		Seat Height	35.2 in
Front Suspension / Wheel Travel	Double wishbone, adjustable spring preload/6.9 in	Estimated Dry Weight	685.8 lb**
Rear Suspension / Wheel Travel	Double wishbone, adjustable spring preload/7.4 in	Curb Weight	732.1 lb*
Front Tires	AT 25 x 8-12	Wheelbase	50.6 in
Rear Tires	AT 25 x 10-12	Instruments	Digital speedometer, 2WD/4WD drive indicator, fuel gauge, odometer, dual trip meters, dual hour meter, clock (12h/24h), battery voltage, Kawasaki service reminder, oil change reminder, high beam, neutral, reverse, and warning lights (engine, coolant temperature, CVT, oil, EPS, and battery voltage)
Front Brakes	Dual hydraulic 176mm discs with 2-piston calipers	Special Features	2,500-lb winch with synthetic rope, Front brush guard, Hand guards, Full-color TFT Instrumentation w/ Smartphone Connectivity via RIDELOGY THE APP POWERSPORTS, KQR™ system
Rear Brakes	Sealed, oil-bathed, multi-disc with independent park brake	Color Choices	TRUETIMBER® STRATA
Ground Clearance	9.0 in/9.7 in (max preload)	Warranty	12 Month Limited Warranty
Starting System	Electric		
Fuel Capacity	5.0 gal		
Steering	Rack-and-pinion w/ Electric Power Steering (EPS)		

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

**Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

¹This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Warning: ATVs can be hazardous to operate. For your safety: Always wear a helmet, eye protection, and protective clothing. Never carry a passenger. Never ride under the influence of drugs or alcohol. Never ride on public roads or pavement. Avoid excessive speeds and stunt driving. Be extra careful on difficult terrain. Kawasaki ATVs with engines over 90cc are intended for use only by persons 16 years of age or older. Kawasaki also recommends that all ATV riders take a training course. For more information, see your dealer, call the ATV Safety Institute at 1-800-887-2887, or go to www.atvsafety.org. ©2026 Kawasaki Motors Corp., U.S.A.

™/® & © 2026 TrueTimber Outdoors Holding Company, LLC. Manufactured and/or distributed under official license by Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit bermuda.kawasaki-la.com for full product details.